

ACP-4360

4U Rackmount Chassis with 6 Hot-Swap SAS / SATA Trays for RAID

NEW

PICMG 1.0

PICMG 1.3



Features


- Supports up to 6 SAS/SATA HDDs, which can be hot-swappable if a SATA RAID card is used
- Supports either an ATX motherboard or a PICMG backplane up to 15 slots
- Supports one slim optical disk drive and one 3.5" FDD or internal HDD
- LED indicators for LAN connectivity and alarm notification for redundant power supply, HDD activity, system fan and in-chassis temperature
- Reusable, front-accessible filters for easy maintenance

Specifications

Drive Bay	Slim Optical Drive (Front-accessible)	Front-accessible
	3.5"	1
Cooling	Fan	6 SAS/SATA HDDs + 1
	Air Filter	1 (12 cm / 114 CFM) + 2 (8 cm / 47 CFM each) for SAS/SATA storage unit
Front I/O Interface	USB	Yes
Miscellaneous	LED Indicators	2
	Rear Panel	System: Power, HDD (for IDE drives only), fan, temperature, LAN1 and LAN2 SAS/SATA HDD trays: HDD power and activity Backplane version: One D-Sub 9-pin opening Motherboard version: Five D-Sub 9-pin and one 68-pin SCSI openings
Environment	Temperature	Operating: 0 ~ 40° C (32 ~ 104° F) Non-Operating: -20 ~ 60° C (-4 ~ 140° F)
	Humidity	10 ~ 85% @ 40° C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms
	Shock	2 G
	Shock	10 G (with 11 ms duration, half sine wave) 30 G
Physical Characteristics	Dimensions (W x H x D)	482 x 177 x 501 mm (19" x 7" x 19.8")
	Weight	19.0 kg (41.8 lb) / 19.5 kg (42.9 lb)

Dimensions

Unit: mm [inch]



Ordering Information

Part Number	Power Supply
Backplane Version	
ACP-4360BP-00XBE	Without power supply, with ATX switch
ACP-4360BP-40ZBE	PS-400ATX-ZBE
Motherboard Version	
ACP-4360MB-00XBE	Without power supply, with ATX switch
ACP-4360MB-40ZBE	PS-400ATX-ZBE

Power Supply Options

Part Number	Specifications	
	Watts	Input
PS-400ATX-ZBE (ATX, PFC)	400 W	AC 100 ~ 240 V (full range)
PS-500ATX-ZE (ATX, PFC)	500 W	AC 115 ~ 240 V (full range)
PS-700ATX-ZE (ATX, PFC)	700 W	AC 100 ~ 240 V (full range)
RPS-400ATX-ZE (ATX, PFC)	400 W	AC 100 ~ 240 V (full range)

Optional Accessories

Part Number	Description
1990001299	Fan filter 95 x 130 mm
1990001298	Door filter 150 x 68 mm
96RC-SAS-4P-PE-LS	Interface PCIe x 8, 4-port SAS/SATA RAID card with 1 SAS SFF8087 connector
96RC-SAS-8P-PE-LS1	Interface PCIe x 8, 8-port SAS/SATA RAID card with 2 SAS SFF8087 connectors
96CB-SAS-SATA-4P	Mini SAS to 4 SATA + SGPIO cable, 0.8 m

PS. Please must use 96CB-SAS-SATA-4P to ensure the LEDs on HDD trays function correctly.