

ADAM8253-1DP10

ADAM8208-1CA00

ADAM8253-1CA01

Profibus-DP Slave Fiber Optic Module

CANopen Master Module

CANopen Coupler



ADAM8253-1DP10



Specifications

- **Interface** LWL: POF/HCS
- **Baudrate** 9.6 K up to 12 Mbps
- **Connectable Slaves** 32
- **Max. Input** 152 byte
- **Max. Output** 152 byte
- **Supply Voltage** 24 V_{DC}
- **Current Consumption** 800 mA



ADAM8208-1CA00



Specifications

- **Interface** 9-pin SubD
 - **Baudrate** 10 K up to 1 Mbps
 - **Connectable Slaves** 126
 - **Parameter Memory** MMC card
 - **Max. Input** 256 byte
 - **Max. Output** 256 byte
 - **Supply Voltage Int. Bus** 5 V_{DC}
 - **Current Consumption** 380 mA
- Int. bus



ADAM8253-1CA01



Features

- Easy error search via diagnostic LEDs
- Emergency message, node guarding, heartbeat
- PDD linking & mapping
- CANopen slave up to 1 Mbaud baudrate

Specifications

- **Interface** 9-pin SubD
- **Baudrate** 10 K up to 1 Mbps
- **Connectable Slaves** 32
- **Max. Input** 80 byte
- **Max. Output** 80 byte
- **Supply Voltage** 24 V_{DC}
- **Current Consumption** 700 mA

Ordering Information

- **ADAM8253-1DP10** Profibus-DP Slave Fiber Optic Module

Ordering Information

- **ADAM8208-1CA00** CANopen Master Module

Ordering Information

- **ADAM8253-1CA01** CANopen Coupler