ADAM-6510 ADAM-6520

4-port Industrial 10 Mbps Ethernet Hub 5-port Industrial 10/100 Mbps Ethernet Switch





C ∈ FCC

C ∈ FCC

ADAM-6510

Specifications

Interface 10Base-T standard network Port 4 x 10 Mbps, 1 x 10 Mbps uplink

Connector **RJ-45**

IEEE 802.3, IEEE 802.3u Compatibility

 Surge Protection 3000 V_{DC}

(Power)

Power, 10 Mbps Unregulated 10~ 30 V_{DC} Power Requirements

Power Consumption 2 W (typical)

ABS with captive mounting hardware Case DIN-rail, panel mounting, piggyback stack Mounting

■ Operating Temperature -10~ 70° C Storage Temperature -20~ 80° C

 Operating Humidity 20~95% (non-condensing) Storage Humidity 0 ~ 95% (non-condensing)

Ordering Information

 ADAM-6510 4-port Industrial 10 Mbps Ethernet Hub

ADAM-6520

Specifications

Interface 10/100Base-T standard network Port 5 x 10/100 Mbps (ADAM-6520)

Connector **RJ-45**

Compatibility IEEE 802.3, IEEE 802.3u

 Surge Protection 3000 V_{DC}

(power)

Power, 10/100 Mbps Unregulated 10 ~ 30 V_{nc} **Power Requirements** Power Consumption 2.4 W (typical)

Case ABS with captive mounting hardware DIN-rail, panel mounting, piggyback stack Mounting

• Operating Temperature $-10 \sim 70^{\circ}$ C Storage Temperature -20 ~ 80° C

 Operating Humidity 20 ~ 95% (non-condensing) Storage Humidity 0 ~ 95% (non-condensing)

Ordering Information

 ADAM-6520 5-port Industrial 10/100 Mbps Ethernet Switch