

# Thermo Recorder TR7A series

New



## TR71A

Temperature 2ch  
Compliant with VFC Guidelines

## TR72A

Temperature 1ch  
Humidity 1ch

## TR72A-S

Temperature 1ch  
Humidity 1ch  
High-Precision type

## For Easy Worldwide Access and Notification

Our new TR7A includes multi-communication methods and auto-upload of data to the cloud function plus a new array of features and functions.




### Two Tier Display Plus Warning Notification

View Measurements of Two Channels  
View Upper and Lower Limit Alarms



### MAX / MIN Display

Automatic clearing at regular intervals,  
so you can see the max/min values for each day.



### Large Storage Capacity 30,000 readings per channel

Can store up to 3.5 years of data in the device



### Improved Storage Performance

Even if battery power is completely gone,  
no recorded data will be lost.



### Improved Security

Network communication with server via HTTPS  
Planned WPA2-EAP support for Wireless LAN



### For Vaccine Temperature Management

[Vaccine Mode] settings for VFC  
compatible model TR71A

## Measure / Record




## Wireless LAN

(Automatic Data Upload)



## USB



	TR71A	TR72A	TR72A-S
Measurement Channels	Temperature 2ch	Temperature 1ch, Humidity 1ch	Temperature 1ch, Humidity 1ch (High-Precision Type)
Sensor	Thermistor	Thermistor	Thermistor
Measurement Units	°C, °F	°C, °F	°C, °F
Measurement Range	Internal Sensor	-10 to 60 °C *1	-
	External Sensor	-40 to 110 °C (Supplied Sensor) -60 to 155 °C (Optional Sensor: Fluoropolymer Coated Type)	0 to 55 °C
Accuracy	Avg. ± 0.3 °C at -20 to 80 °C Avg. ± 0.5 °C at -40 to -20 °C, 80 to 110 °C	±0.5 °C	±0.3 °C at 10 to 40 °C ±0.5 °C all other temperatures
Measurement Resolution	0.1 °C	0.1 °C	0.1 °C
Responsiveness	(Supplied Sensor) Thermal Time Constant: Approx. 75 sec. Response Time (90%): Approx. 190 sec.	Response Time (90%): Approx. 7 min.	Response Time (90%): Approx. 7 min.
Logging Capacity	30,000 data sets (One data set consists of readings for all channels.)		
Recording Interval	Select from 15 choices: 1, 2, 5, 10, 15, 20, 30 sec. or 1, 2, 5, 10, 15, 20, 30, 60 min.		
Recording Mode	Endless (Overwrite oldest data when capacity is full) or One Time (Stop recording when capacity is full)		
LCD Display Items	Measurements, Battery Warning Mark, etc. - Measurements: Ch1 & Ch2 current values / Ch1 Max & Min values / Ch2 Max & Min values - Display Pattern: Alternating or Fixed display		
Auto-upload Interval	Select from 15 choices: OFF (No auto-upload), 1, 2, 5, 10, 15, 20, 30 min. or 1, 2, 3, 4, 6, 12, 24 hrs.		
Communication Interfaces	Wireless LAN Communication IEEE 802.11b/g/n (2.4GHz only) Security : WPA/WPA2-PSK(AES/TKIP) WPS 2.0 : Push Button Configuration Protocol *3: HTTP, HTTPS, DHCP, DNS Bluetooth Communication *4 Bluetooth 4.2 (Bluetooth low energy) USB Communication USB 2.0 (Mini-B connector)		
Power *5	Battery: AA Alkaline LR6 x 2, AA Ni-MH x 2 External: USB Bus 5V 200mA, AC Adaptor AD-05A2 or AD-05C2		
Battery Life *6	Approx. 10 days to 15 months *7		
Dimensions	H 58 mm x W 78 mm x D 26 mm		
Weight	Approx. 55 g		
Operating Environment	Temperature: -10 to 60 °C, Humidity: 90 %RH or less (no condensation)		
Accessories	Temperature Sensor TR-0106 x2	Temperature-Humidity Sensor THA-3001 x1	High Precision Temperature-Humidity Sensor SHA-3151 x1
Software	AA Alkaline Battery LR6 x 2, Registration Code Label, USB Mini-B Cable US-15C, Manual Set (Warranty Included)		
	PC Software (Windows) *8: TR7 for Windows, T&D Graph For compatible OS versions, please refer to the Software page of our website at <a href="http://tannd.com/software/">tannd.com/software/</a> Software/App to be available within 2021: PC Software (Windows): T&D Data Server Mobile Application (iOS, Android): T&D Thermo		

\*1: When Auto Upload is used frequently, the measurement of the internal sensor may rise by around 0.3°C. When using external power, the data logger itself generates heat and the internal sensor will report a temperature much higher than ambient; we recommend using an external temperature sensor in this case.

\*2: When continually used in environments with temperatures above 60 °C, accuracy of humidity measurements will decrease over time. Also, humidity cannot be measured at temperatures below -20 °C.

\*3: Client function. HTTP(S) proxy supported.

\*4: Bluetooth will be used to make settings and view data on iOS and Android devices with the mobile app (to be available within 2021).

\*5: When using external power, the internal temperature of the logger rises.

\*6: Battery life is highly dependant on the Auto-upload interval; at 1 min will give 10 days of usage, and at 12 hours or more will yield the maximum lifetime. Other influential factors include LAN environment, ambient temperature, recording interval, and battery performance. All estimates are based on operations carried out with a new battery and are in no way a guarantee of actual battery life.

\*7: Shows the estimated battery life with Auto-Upload ON.

\*8: For installation, it is necessary to have Administrator (Computer Administrator) rights.

The specifications listed above are subject to change without notice.



**T&D Corporation**

817-1 Shimadachi, Matsumoto, Nagano Japan 390-0852

Please send your inquiries to:

E-mail : [sales@tannd.com](mailto:sales@tannd.com)

Facsimile : (+81) 263-40-3152

16308230001 (1st Edition)