

EKI-2525P EKI-2525SPI EKI-2526PI

NEW



5-port Industrial PoE Switch

5-port Industrial PoE Switch with 1x100Fx Single-Mode and Wide Temperature

6-port Industrial PoE Switch with Wide Temperature

Features

- Provides 5/6 Fast Ethernet ports with 4 PoE ports with injector function
- Provides 1 x 100Mbps Single-mode SC type fiber optic port (EKI-2525SPI)
- Supports 10/100Mbps Auto Negotiation
- Provides broadcast storm protection
- Supports Ethernet ESD protection
- Provides Slim size, DIN-rail/Wallmount with IP30 metal mechanism
- Supports Redundant 48 V_{DC} power input and P-Fail relay
- Supports operating temperatures from -10 ~ 60° C (EKI-2525P)
- Supports wide operating temperature -40 ~ 75° C (EKI-2525SPI/EKI-2526PI)

Introduction

The EKI-2525P/EKI-2525SPI is a 5-port unmanaged PoE (Power-over-Ethernet) Industrial Ethernet switch and EKI-2526PI is a 6-port unmanaged PoE Industrial Ethernet switch, they support 4 PoE ports which are classified as power source equipments (PSE). The PoE devoces makes centralized power supply come true and provides up to 15.4 watts of power per port. Advantech EKI PoE devices can be used to power IEEE802.3af compliant powered devices (PD) by Ethernet cable and eliminates the need for additional power wiring. Advantech EKI PoE devices come equipped with all the standard features of the EKI family. Furthermore, it offers a 48 V_{DC} redundant power input design (EKI-2525P/EKI-2526PI), and is secured with a double protection mechanism; Power Polarity Reverse Protect and an Overload Current Resettable Fuse. Advantech EKI PoE devices come with compact metal housing that rates IP30 to help against from dusty industrial environments.

Specifications

Communications

- Standard IEEE 802.3, 802.3u, 802.3x, 802.3af
- LAN 10/100Base-T(X)
- Transmission Distance Ethernet: Up to 100 m (EKI-2525P/EKI-2526PI)
Single-mode Fiber: Up to 30km (EKI-2525SPI)
- Transmission Speed Up to 100 Mbps

Fiber Optics (EKI-2525SPI)

- Signal Mode 1310nm
- Tx Power: -8/-15 dBm
- Rx Sensitivity: -34dBm
- Parameters: 9/125um

Interface

- Connectors PoE Ports: 4 (Ports 1 ~ 4)
Ethernet x1 (EKI-2525P)
1xSC type fiber connector(EKI-2525SPI)
Ethernet x2 (EKI-2526PI)
- LED Indicators 6-pin removable screw terminal (power & relay)
P1, P2, P-Fail
10/100TX: Link/Activity, Duplex/Collision

Power

- Power Consumption EKI-2525P: 65 W (Full load PoE)
EKI-2525SPI: 62.5 W (Full load PoE)
EKI-2526PI: 62.6 W (Full load PoE)
- Power Input 48 V_{DC} (EKI-2525P/EKI-2526PI), redundant dual inputs
24/48 V_{DC} (EKI-2525PA), redundant dual inputs
- Power Output 15.4 W at 48V (per PoE port)
- Fault Output 1 Relay Output

Mechanism

- Dimensions (W x H x D) 37 x 140 x 95 mm (EKI-2525P/EKI-2525SPI)
48.6 x 140 x 95 mm (EKI-2526PI)
- Enclosure IP30, Metal shell with solid mounting kits
- Mounting DIN-rail, Panel

Protection

- Reverse Polarity Present
- Overload EKI-2525P: 3 A @ 48 V_{DC}
EKI-2525SPI: 3 A @ 48 V_{DC}
EKI-2526PI: 3.5 A @ 48 V_{DC}

Environment

- Operating Temperature -10 ~ 60° C (14 ~ 140° F) (EKI-2525P)
-40 ~ 75° C (-40 ~ 167° F) (EKI-2525SPI/EKI-2526PI)
- Storage Temperature -40 ~ 85° C (-40 ~ 185° F)
- Operating Humidity 5 ~ 95% (non-condensing)
- Storage Humidity 0 ~ 95% (non-condensing)
- MTBF 440,132 hrs

Certifications

- Safety UL 60950-1, CAN/CSA-C22.2 No.60950
- EMC U.S.A.: FCC Part 15 CISPR 22
EU: EN55011, EN61000-6-4
EN55022 Class A,
EN55024
IEC61000-4-2/3/4/5/6/8
EN61000-6-2
- Shock IEC60068-2-27
- Freefall IEC60068-2-32
- Vibration IEC60068-2-6

Ordering Information

- EKI-2525P 5-port PoE Switch
- EKI-2525SPI 5-port PoE Switch w/ 1-port 100Fx SM/ Wide Temp
- EKI-2526PI 6-port PoE Switch w/ Wide Temp



www.bmc.de

Dr. Schetter BMC GmbH

Boschstrasse 12

82178 Puchheim

TEL 089 800 694 - 0

FAX 089 800 694 - 29

