

Power Supplies

PS/2 Power Supply Specifications



PS-400ATX-Z

400W AC-DC ATX Power Supply with PFC

P/N: PS-400ATX-Z							
Input Range	AC 90 ~ 264V @ 47 ~ 63 Hz, full range 8.0/5.0 A						
Output Voltage	+5 V 42A (2.5A Min)	+3.3 V 20A (0.2A Min)	+5 V/3.3 V Total 210W	+12 V 14A (0.5A Min)	-5 V 1A	-12 V 1A	+5 Vsb 1A
MTBF(hours)	100,000						
Safety	UL/cUL(60950 3rd)/TUV/CE/CB/CCC						
Power Module Part No. (Accessories)	--						
Compatible with Advantech Products	IPC-610F/IPC-615/IPC-616/IPC-6908/ACP-4000 P4 ATX M/B supported						



PS-400ATX-DC48

400W DC-DC ATX Power Supply

P/N: PS-400ATX-DC48							
Input Range	DC -36 ~ -72V/ Max. 12A						
Output Voltage	+5 V 42A (2.5A Min)	+3.3 V 20A	+5 V/3.3 V Total 210W	+12 V 14A (0.5A Min)	-5 V 1A	-12 V 1A	+5 Vsb 1A
MTBF(hours)	100,000						
Safety	UL/TUV/CB						
Power Module Part No. (Accessories)	--						
Compatible with Advantech Products	OEM/ODM(P4 ATX M/B supported)						



PS-310-DC48

310W DC-DC AT Power Supply

P/N: PS-310-DC48							
Input Range	DC -38 ~ -58V/Max. 10A						
Output Voltage	+5 V 25A (1A Min)	+3.3 V --	+5 V/3.3 V Total --	+12 V 10A	-5 V 1A	-12 V 5A	+5 Vsb --
MTBF(hours)	100,000						
Safety	UL/CE						
Power Module Part No. (Accessories)	--						
Compatible with Advantech Products	IPC-610/IPC-615/IPC-6908/IPC-602/ACP-2000/ACP-4000						