

SQF-SLM

Half-Slim SATA Module

SQF-SLM (Extreme)

Half-Slim SATA Module

NEW



Features

- MO-297 Half-Slim SATA Module
- Compliant with SATA II and SATA v 2.6 standard
- Built-in EDC/ECC up to 15-bit random bits error per 512 bytes
- Universal wear-leveling and bad block management
- Shock resistance, anti-vibration and low power consumption
- GUI management tool & software API package

Specifications


Connector Type	Standard 7+15-pin SATA connector
Flash type	SLC
Capacity	2 to 16GB
Transfer Mode	SATA II (3.0 Gbps)
Sustained R/W Performance (*)	4 channel: 95/50 MB/sec 2 channel: 45/25 MB/sec
Operating Temperature	Commercial grade: 0 to +70° C Industrial grade: -40 to +85° C
Shock Resistance	1,500 G, peak / 0.5 ms
Vibration Resistance	20 G, peak / 80 ~ 2000 Hz
Endurance	2,000,000 program/erase cycles
MTBF	> 2,000,000 hours
Dimension (mm)	54.0 x 39.0 x 4.5

(*) These values are for reference only; they may change according to the flash memory used.

Ordering Information

PN	Description
SQF-SLMS2-2G-R2C	Advantech SQFlash SATA Slim 2 GB SLC, 2-CH (0 ~ 70° C)
SQF-SLMS4-XG-R2C	Advantech SQFlash SATA Slim 4/8/16 GB SLC, 4-CH (0 ~ 70° C)
SQF-SLMS2-2G-R2E	Advantech SQFlash SATA Slim 2 GB SLC, 2-CH (-40 ~ 85° C)
SQF-SLMS4-XG-R2E	Advantech SQFlash SATA Slim 4/8/16 GB SLC, 4-CH (-40 ~ 85° C)

NEW



Features

- MO-297 Half-Slim SATA Module
- Compliant with SATA II and SATA v 2.6 standard
- Support 48/32/28 bit ECC correct per 2K Byte data
- Universal wear-leveling and bad block management
- Shock resistance, anti-vibration and low power consumption
- GUI management tool & software API package

Specifications

Connector Type	Standard 7+15-pin SATA connector
Flash type	SLC / MLC
Capacity	SLC: 4 to 32GB MLC: 4 to 64GB
Transfer Mode	SATA II (3.0 Gbps)
Sustained R/W Performance (*)	SLC: 145/100 MB/sec (32GB up to 210/175) MLC: 135/90 MB/sec (64GB up to 200/175)
Operating Temperature	Commercial grade: 0 to +70° C Industrial grade: -40 to +85° C
Shock Resistance	1,500 G, peak / 0.5 ms
Vibration Resistance	20 G, peak / 80 ~ 2000 Hz
Endurance	2,000,000 program/erase cycles
MTBF	> 2,000,000 hours
Dimension (mm)	54.0 x 39.0 x 4.5

(*) These values are for reference only; they may change according to the flash memory used.

Ordering Information

PN	Description
SQF-SLMS4-XG-S5C	Advantech SQFlash SATA Slim 4/8/16/32 GB SLC, 4-CH (0 ~ 70° C)
SQF-SLMS4-XG-S5E	Advantech SQFlash SATA Slim 4/8/16/32 GB SLC, 4-CH (-40 ~ 85° C)
SQF-SLMM4-XG-S5C	Advantech SQFlash SATA Slim 4/8/16/32/64/128 GB MLC, 4-CH (0 ~ 70° C)
SQF-SLMM4-XG-S5E	Advantech SQFlash SATA Slim 4/8/16/32/64/128 GB MLC, 4-CH (-40 ~ 85° C)