



Mechanical Data

Case Style : IP-68 Instrument
Height : 82mm / 3.3"
Width : 60mm / 2.6"
Depth : 40mm / 1.6"
Mounting holes : 4.2mm / 0.16"
diameter
70mm / 2.8"
separation

Features

Memory Size : 8k (Non-volatile)
No. of Readings : 7900
Resolution : 8 bit
Delayed Start : Relative / Actual
up to 45 days
Trigger Start : Magnetic reed switch
Stop Options : When Full
After n Readings
Never (Wrap around)
Reading Types : Actual, Min, Max.
Logging Interval : 1 sec to 10 days
Offload : While stopped or
when logging in
minute multiples
Alarms : Two, fully
Programmable
Functional Range : -40°C → +85°C /
-40°F → +185°F
IP Rating : IP68
Battery Life : Up to 3 years
Offload Speed : Approx 20 Seconds
Offload Method : Close Proximity

Note:

Functional Range describes the range over which the logger will function, **not** the sensor range over which it will record.

Sensor Details

Range : -40°C → +85°C /
-40°F → +185°F
Sensor Type : 10k NTC Thermistor
(Encapsulated)
Sensor location : Internally mounted
Response Time : 15 min to 90% in air
(Approx)
Sensor accuracy : ± 0.2°C / ± 0.36°F
From 0°C → 70°C /
32°F → 158°F
Resolution : < 2°, 60° → 85°C
< 1°, 35° → 60°C
< 0.5°, -25° → 35°C
< 1°, -40° → -25°C

Approvals

This equipment complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause any harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This product is manufactured by Gemini Data Loggers (UK) Ltd to BS EN ISO 9001:2000 (Certificate No. 6134), and is CE approved to EN50081 part 1:1992 and EN50082 part 1 and 2:1992/95 with any standard leads or probes supplied.



UKAS traceable calibration certificates are available on individual units.

Special Notes

Battery replacement recommended every 2 years. We recommend using only replacement batteries from your Tinytag distributor.

When using the units at low temperatures, condensation may form. Before opening the case for any reason, allow the units to reach room temperature.

Interface Information and Related Products

To use your Tinytag Data Logger you will require:

Tinytag Pad base station (ACS-3020), PC with GLM (SWCD-0009) or Easyview (SW-0500)

Further Related Products:

SER-9560 Tinytag Extra Service Kit including battery, seal and silica gel pack.