

Data Logger for Cloud Storage

TR-7wf/nw Series Features and Specs

Measurement Items

Temperature
Humidity

Data Collection

LAN / USB Connection
Direct Communication
with Smart phone/Tablet


Data Access

T&D WebStorage Service,
Intranet, Local PC

Warning Notification

E-mail

Temperature and Humidity Data Logger made for the Cloud. Recorded data can automatically be uploaded via wireless or wired LAN to our free cloud service "T&D WebStorage Service" where it can be accessed from anywhere you have a connection. It is also possible to connect directly to a PC via USB and the TR-7wf allows for direct wireless communication with smart phones and other portable devices.



Model	Measurement Items	Measurement Range	Notes
TR-71wf / nw	Temperature 2ch	-60 to 155 °C	The measurement range depends on the sensor type. Wide selection of optional sensors available
TR-72wf / nw	Temperature / Humidity 1ch Each	0 to 55 °C / 10 to 95%RH	
TR-72wf-H / nw-H	Temperature / Humidity 1ch Each	-30 to 80 °C / 0 ~ 99%RH	The supplied sensor for the H model provides higher accuracy to ±2.5%RH
TR-75wf / nw NEW!	Temperature 2ch (Thermocouple)	-199 ~ 1760 °C	For use with Thermocouple Sensor Types: K, J, T, E, S, R

Sending Warning Report Mails

Upon receiving warning information from the target device T&D WebStorage Service will send out a warning e-mail to the set recipients

1.5 Years of Operation with just Two Batteries

With just two AA batteries the logger can be used for about 1.5 years.

* Actual battery life is not guaranteed.

Large Logging Capacity: 8000 Data Sets

It is possible to record up to 8000 sets of data measurements in two separate channels. That means at a recording interval of 60 minutes you can keep on recording for one year before reaching capacity.

Easy Operation via Front Buttons

It is possible to start and stop recording, change recording interval, and make the auto-upload setting from the buttons on the face of the logger.

TR-7wf/nw Series - Specifications

	TR-71wf / 71nw	TR-72wf / 72nw		TR-72wf-H / 72nw-H		TR-75wf / 75nw
Measurement Channels	Temperature 2ch (Internal 1ch / External 2ch)	Temperature 1ch, Humidity 1ch (External)		Temperature 1ch, Humidity 1ch (External)		Temperature 2ch
Sensor	Thermistor	Thermistor	Polymer Resistance	Platinum Resistance	Electrostatic Capacitance	Thermocouple: Type K, J, T, E, S, R
Measurement Units	°C, °F	°C, °F	%RH	°C, °F	%RH	°C, °F
Measurement Range	Internal Sensor	-10 to 60 °C (*1)	-	-	-	-
	External Sensor	-40 to 110°C (Supplied Sensor) -60 to 155°C (Optional Sensor)	0 to 55 °C	10 to 95 %RH	-30 to 80 °C	0 to 99 %RH
Accuracy	Avg. ±0.3°C at -20 to 80 °C Avg. ±0.5°C at -40 to -20 °C 80 to 110 °C	±0.5°C	±5 %RH at 25°C, 50%RH	±0.3°C at 0 to 50 °C ±0.5°C all other temperatures	±2.5 %RH at 25 °C, 10 to 85 %RH ±4.0 %RH at 25°C, 0 to 10%RH or 85 to 99 %RH For temperatures other than 25 °C and between 0 °C and 80 °C, add ±0.1%RH per degree differ- ence from 25. Humidity Hysteresis: ±1.5 %RH or lower (*2)	Thermocouple Measurement : K, J, T, E ± 0.5°C ± 0.3% of reading at -100°C or above S, R ± 1.5°C ± 0.3% of reading at 100°C or above Cold Junction Compensation: ±0.5°C in operating environment of 10 to 40 °C ±0.8°C in other operating environment
Measurement Resolution	0.1 °C	0.1°C	1 %RH	0.1°C	0.1 %RH	K, J, T, E : 0.1 °C S, R : approx. 0.2 °C
Responsiveness	Thermal Time Constant: Approx. 75 sec. Response Time (90%) : Approx. 190 sec.	Response Time (90%) : Approx. 7 min.		Response Time (90%) : Approx. 7 min.	Response Time (90%) : Approx. 20 sec.	-
LCD Display Items	Measurements (fixed or alternating display), Battery Warning Mark, etc.					
Logging Capacity	8,000 data sets (One data set consists of readings for all channels in that type of unit.)					
Recording Interval	Select from 15 choices: 1, 2, 5, 10, 15, 20, 30 sec. or 1, 2, 5, 10, 15, 20, 30, 60 min.					
Recording Mode	Endless (Overwrite oldest data when capacity is full) / One Time (Stop recording when capacity is full)					
Auto-upload Interval	Select from 15 choices: OFF (No auto-upload), 1, 2, 5, 10, 15, 20, 30 min. or 1, 2, 3, 4, 6, 12, 24 hrs.					
Communication Interfaces	Wireless LAN Communication for TR-7wf: Standard: IEEE 802.11b Security (*3) : WEP (64 bit/128 bit), WPA-PSK (TKIP) , WPA2-PSK (AES) WPS 2.0 : Push Button Configuration, Protocol: HTTP (*4), DHCP, DNS Wired LAN Communication for TR-7nw: 100BASE-TX/10BASE-T (RJ45 Connector) Protocol: HTTP (*4) , DHCP, DNS USB Communication: USB 2.0 (Mini-B connector)					
Power (*5)	Battery: AA Alkaline x 2 (AA Ni-MH batteries may also be used), External: USB Bus (5V 200mA), AC Adaptor (AD-05A2 or AD-05C2), PoE IEEE 802.3af (TR-7nw only)					
Battery Life (*6)	With LAN communication: Approx. 10 days to 1.5 years Ex: Approx. 10 days when Auto-upload Interval is 1 min, 1 yr when 1 hr, 1.5 yrs when 12 hrs or more Without LAN communication: Approx. 1.5 years					
Dimensions	H 58 mm x W 78 mm x D 26 mm					
Weight	Approx. 55 g					
Operating Environment	Temperature -10 to 60°C (*7), Humidity 90 %RH or less (no condensation)					
Accessories	Temperature Sensor TR-0106 x2	Temperature-Humidity Sensor THA-3001 x1	High Precision Temperature-Humidity Sensor HHA-3151 x1	-		
	AA Alkaline Battery (LR6) x 2, Registration Code Label, USB Mini-B Cable (US-15C), Manual Set (Warranty Included)					
Software Com- patible OS (*8)	TR-7wf/nw for Windows / T&D Graph / T&D Data Server (For PC) Microsoft Windows 10 32 / 64 bit Microsoft Windows 8 32 / 64 bit Microsoft Windows 7 32 / 64 bit Microsoft Windows Vista 32 bit SP1 or later (T&D Data Server not compatible) T&D Thermo (For Smart phone, Tablet) Android OS, iOS (For the compatible versions, please refer to our website.)					
Display Languages (*9)	English					

*1: When Auto Upload is used frequently, the measurement of the internal sensor may rise by around 0.3°C .

When using external power, the data logger itself generates heat and the internal sensor will report a temperature much higher than ambient; we recommend using an external temperature sensor in this case.

*2: When used in environments where temperature and humidity are over the values of 50°C 75%, 60°C 50%, 70°C 35%, and 80°C 25%, sensor hysteresis may fluctuate by values greater than ±1.5%RH. Under certain circumstances, it may take some time to return to normal measurement capability.

*3: The WPS feature is not available when WEP (64bit/128bit) or WPA-PSK (TKIP) is selected in Access Point Settings. If you wish to use the WPS feature, please select WPA2-PSK (AES) or disable wireless security.

*4: HTTP client. Proxy supported. (for firmware version 1.05 or above for TR-71wf/72wf).

*5: When using external power, the internal temperature of the logger rises.

*6: Battery life varies depending upon multiple factors including frequency of communication, LAN environment, ambient temperature, recording interval, and battery performance. All estimates are based on operations carried out with a new battery and are in no way a guarantee of actual battery life.

*7: -10 to 45°C when using external power (TR-7nw only).

*8: For installation, it is necessary to have Administrator (Computer Administrator) rights.

*9: We recommend using an operating system in the same language as the display language. Operation in different languages is not guaranteed.

The specifications listed above are subject to change without notice.