

UNO-1150G/GE

AMD Geode™ LX800 DIN-rail PCs
with 2 x LAN, 3 x COM, PCI-104

NEW



UNO-1150G

UNO-1150GE



Features

- Onboard AMD Geode LX800 500 MHz processor
- One RS-232 and two RS-232/422/485 ports with automatic flow control.
- Two 10/100 Base-T RJ-45 ports
- Two USB, audio and internal CompactFlash®
- Compact size, small foot print, saves space and front accessible for easy wiring
- DIN-rail design for easy installation in field cabinet
- Wide operating temperature range
- Windows® CE 6.0, Windows XP Embedded, and Linux ready solution
- Onboard system & I/O LED indicators
- Fanless desing with no internal cabling
- Isolation between chassis and power ground

Introduction

UNO-1150G/GE are DIN-rail mounted PCs that provide several serial communication ports and Ethernet interfaces. Their compact size, small footprint and front-accessibility allow easy installation in field cabinets and help to save spaces. With rich OS and driver supports, such as Windows XP Embedded, WinCE 6.0 and embedded Linux, users can integrate applications easily with a platform that can provide versatile functions to fulfill diverse requirements.

Specifications

General

- Certification** CE, FCC Class A, UL, CCC
- Dimension (W x H x D)** UNO-1150G: 71 x 152 x 139 mm (2.8" x 6" x 5.5")
UNO-1150GE: 96.5 x 152 x 139 mm (3.8" x 6" x 5.5")
- Enclosure** Aluminum + SECC
- Mounting** DIN-rail, Wallmount
- Power Consumption** 15 W (Typical)
- Power Requirement** 9 ~ 36 V_{DC} (e.g. +24 V @ 1 A) (Min. 24 W), AT
- Weight** UNO-1150G: 1.6 kg
UNO-1150GE: 2.0 kg
- OS Support** WES Windows XP Embedded, Windows 2000 & XP, Windows CE 5.0/6.0, Linux
- System Design** Fanless with no internal cabling
- Remote Management** Built-in Advantech DiagAnywhere agent on Windows CE / XPe

System Hardware

- CPU** AMD Geode LX800 500 MHz
- Memory** Onboard 256 MB DDR SDRAM
- Indicators** LEDs for Power, IDE, LAN (Active, Status) and Serial (Tx, Rx)
Buzzer for Diagnosis (programmable)
- Keyboard/Mouse** 1 x PS/2
- Storage** SSD: 1 x internal type I/II CompactFlash® slot
HDD: 2.5" SATA HDD bracket (UNO-1150GE)
2 x PCI-104 slot, supports 3.3 V & +5 V
(Only for UNO-1150GE, one PCI-104 left while using HDD)
- PC/104 Slot**
- Mini PCI** 1 x Mini PCI (UNO-1150GE)
- Display** DB15 VGA connector, supports up to 1024 x 768 @ 60 Hz
- Audio** Line in, Line out
- Watchdog Timer** Programmable 256 level timer interval, from 1 to 255 sec

I/O Interface

- Serial Ports** 2 x RS-232 (one pin header reserved),
2 x RS-232/422/485 with DB9 connectors,
Automatic RS-485 data flow control
RS-232/422/485 ports support hardware 128 byte FIFO
- Serial Port Speed** RS-232 port: 50 ~ 115.2 kbps
RS-232/422/485 port: RS-232, 300 ~ 115.2 kbps
RS-232/422/485 port: RS-422/485, 300 ~ 921.6 kbps (Max)
- LAN** 2 x 10/100 Base-T RJ-45 ports
- USB** 2 x USB, OpenHCI, Rev. 2.0 compliant

Environment

- Operating Temperature** (IEC 60068-2-2, 100% CPU/ I/O loading)
-10 ~ 60° C (14 ~ 140° F)
- Storage Temperature** -20 ~ 80° C (-4 ~ 176° F)
- Operating Humidity** 20 ~ 95% (non-condensing)
- Storage Humidity** 0 ~ 95% (non-condensing)
- Shock Protection** IEC 60068-2-27
CompactFlash®: 50 G @ wall mount, half sine, 11 ms
HDD: 20 G @ wall mount, half sine, 11 ms
(UNO-1150GE)
- Vibration Protection** IEC 60068-2-64 (Random 1 Oct./min, 1hr/axis.)
CompactFlash®: 2 Grms @ 5 ~ 500 Hz
HDD: 1Grms@ 5 ~ 500 Hz (UNO-1150GE)

Ordering Information

- UNO-1150G-G30E** LX800 MHz, 256 MB DIN-rail PC
- UNO-1150GE-G30E** LX800 MHz, 256 MB DIN-rail PC w/PCI-104

Accessories

- UNO-FPM11-BE** UNO-1100 Series VESA Mount kit
- PCLS-DIAGAW10** Advantech Remote Monitoring & Diagnosis Utility

1

Operator Panels

2

Fanless Panel PCs

3

Panel Computers

4

Display Solutions

5

Ethernet Switches

6

Device Servers

7

Serial Comm. Cards

8

Video Surveillance

9

Pre-Configured Systems

10

IPC Chassis

11

SBCs and Backplanes

12

Industrial Motherboards

13

Embedded IPCs

14

Mobile Computers

15

IPC Peripherals

16

DAQ

17

Signal Conditioning

18

USB DAQ