


UNO-2050E

AMD GX2 UNO w/2 x LAN, 4 x COM, 16 DI/O

NEW



Features

- Onboard GX2 400 MHz
- Two RS-232 and two-isolated RS-232/422/485 with automatic flow control
- Two 10/100 Base-T RJ-45 port
- Isolated 8-ch DI and 8-ch DO with counter and timer
- Windows® CE 5.0, Windows XP Embedded SP2, and Linux ready solution

Introduction

UNO-2050E is an X86-grade platform with dual LAN and 16-channel isolated digital I/O and timer/counter. In addition, it also provides two RS-232 and two isolated RS-232/422/485 communication ports with RS-485 automatic flow control functionality. Therefore, the UNO-2050E is an ideal solution for embedded controllers.

UNO-2050E comes with a built-in Windows CE solution offering a pre-configured image with optimized onboard device drivers. Microsoft Windows CE is a compact, highly efficient, real-time operating system designed for embedded systems without mechanical HDD limitations. To expand storage capability, the UNO-2050E allows the addition of an external 2.5" HDD using Advantech's UNO HDD expansion kit. It can be used for large data backup requirements and popular OS installations such as Microsoft Windows and Linux OS. Significant anti-vibration (1G w/HDD) is maintained even with the mechanical HDD inside. UNO-2050E is the perfect embedded application ready platform that can shorten development time and offer a rich networking interface to fulfill diverse application requirements.

Specifications

General

- **Dimensions (W x D x H)** 188.8 x 106.5 x 35.5 mm (7.5" x 4.2" x 1.4")
- **Enclosure** Aluminum
- **Mounting** Wall, DIN 35 rail
- **Power Consumption** 15 W (Typical)
- **Power Input** 9 ~ 36 V_{DC} (e.g. +24 V @ 1 A) (Min. 24 W), AT
- **Weight** 0.8 kg
- **OS Support** Windows XP Embedded, Windows 2000 & XP, Windows CE 5.0, Linux

System Hardware

- **CPU** AMD GX2 400 MHz
- **Memory** 256 MB DDRRAM on board
- **Indicators** LEDs for power, IDE, programmable diagnostic LED, and one programmable buzzer.
- **Keyboard/Mouse** 1 x PS/2
- **Storage** SSD: 1 x internal type I/II CompactFlash® slot
HDD: expansion kit for one standard 2.5" HDD (Optional)
- **VGA** DB15 VGA connector
- **Watchdog Timer** Programmable

Communications

- **Counter/Timer** 2 x 16-bit: counter source: DI6 & DI7, Pulse output: DO6 & DO7. Can be cascaded as one 32-bit counter/timer, Down counting, preset counting value, interrupt handling, Timer time base: 100/10/1 kHz, 100 Hz
- **Digital Inputs** 8 ch. wet contact after 8 ch. 2,000 V_{DC} isolation, 2,000 V_{DC} ESD protection, 70 V_{DC} over-voltage protection
0 ~ 50 V_{DC} input range and 10 kHz speed; Interrupt handling.

- **Digital Outputs** 8 ch. 2,000 V_{DC} isolation and 200 mA max/channel sink current. Keeps output status after system hot reset.
5 ~ 40 V_{DC} output range and 10 kHz speed
- **LAN** 2 x 10/100Base-T with RJ-45 port
- **Serial Ports** 2 x standard RS-232 (COM1/COM2)
2 x isolated RS-232/422/485 (COM3/COM4)
Automatic RS-485 data flow control
RS-232/422/485 (COM3/COM4) with 2000 V_{DC} (EFT) surge protection & 2000 V_{DC} isolation
RS-232: 50 ~ 115.2 kbps (COM1/COM2)
50 ~ 230.4 kbps (COM3/COM4)
RS-422/485: 50 ~ 921.6 kbps (Max.)
- **Serial Port Speed**

Environment

- **Humidity** 95% @ 40° C (non-condensing)
- **Operating Temperature** -10 ~ 55° (14 ~ 131° F)
- **Shock Protection** IEC 68 2-27
CompactFlash: 20 G @ DIN, half sine, 11 ms, 50 G @ Wall/Panel, half sine, 11 ms
- **Vibration Protection** IEC 68 2-6
CompactFlash: 2 Grms @ sine, 5 ~ 500 Hz, 1 Oct./min, 1hr/axis.
HDD: 1 Grms @ sine, 12 ~ 300 Hz, 1 Oct./min, 1hr/axis.

Ordering Information

- **UNO-2050E-IDA0E** GX2 400 M, 256 MB RAM UNO-2050E

Accessories

- **UNO-HD20-AE** UNO-2000 HDD expansion kit
- **UNO-FPM21-AE** UNO & FPM integration kit
- **UNO-ADAM42-AE** UNO-2000 & ADAM integration kit