



### Mechanical Data

Case Style : IP65 noryl  
Colour : Blue/orange  
food grade  
Diameter : 60mm / 2.36  
Length : 84mm / 3.31  
Width : 76mm / 2.99  
Depth : 35mm / 1.38  
Weight : 85g / 3 oz.

### Features

Memory Size : 16k (Non-volatile)  
Display : 4 digits + indicators  
No. of Readings : 14800 (approx)  
Resolution : 8 bit  
Trigger Start : Magnetic reed switch  
Delayed Start : Relative / Actual  
up to 45 days  
Stop Options : When Full  
After n Readings  
Never (Wrap around)  
Reading Types : Actual, Min, Max.  
Logging Interval : 1 sec to 10 days  
Offload : While stopped or  
when logging in  
minute multiples  
Alarms : Two, fully  
Programmable  
Functional Range : -40°C to +85°C /  
-40°F to +185°F  
Display Functions : -20°C to +70°C /  
-4°F to 158°F  
IP Rating : IP65 splashproof  
Battery Life : Up to 3 years

#### Notes:

Battery replacement is recommended every 2 years. It may be replaced with Saft 3.7V 1/2AA Lithium cells. Stop the unit logging before replacing the battery. Functional Range describes the range over which the logger will function, **not** the sensor range over which it will record.

### Sensor Details

Range : -30°C to +50°C /  
-22°F to +122°F  
Sensor Type : Standard Probe with  
10k NTC Thermistor  
Logger resolution : 0.25°C at 0°C /  
0.45°F at 32°F  
Display resolution : 0.5°C /

Sensor Probe choice depends on the application. See individual data sheets for detailed probe specifications.

### Approvals

This equipment complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause any harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This product is manufactured within the Orion Group to ISO EN 9002 part 2 (Certificate No. 6134), and is CE approved to EN50081 part 1:1992 and EN50082 part 1 and 2:1992/95 with any standard leads or probes supplied.



NAMAS traceable calibration certificates are available on individual units.

### Special Notes

When using the units at low temperatures, condensation may form. Before opening the case for any reason, allow the units to reach room temperature. The IP65 rating is only valid when the connector cap is fitted.

Tinyview has the ability to remind the user when calibration is due. The unit can be given a yearly or 6 monthly calibration service, which includes certificate, new battery and seals along with re-setting of the calibration reminder indicator to the next calibration due date.

### Interface Information and Related Products

#### To use your Tiny Data Logger you will require:

A suitable sensor probe for your application. (Includes PB-4724, PB-4730, PB-4750, PB-4770). See individual data sheets for details. Tinytag interface cable (CAB-0007), PC with GLM for Windows™ (SW-0009) or Easyview for Windows 95™ (SW-0500); or Psion handheld computer, with Tinylink version 2.0 or above (SW-1101) and suitable cable (See Tinylink Data Sheet)

#### Further Related Products:

ACS-6000 Trigger Start Magnet  
SER-9550 Tinyview Service Kit including battery, seal and silica gel pack.  
TV-0020 Tinyview Range G (-40°C to +125°C / -40°F to +257°F) for Standard probe. lower resolution but wider range  
TV-0050 Tinyview Range H (-30°C to +50°C / -22°F to +122°F) with internal sensor  
TV-0076 Tinyview Range H (-30°C to +50°C / -22°F to +122°F) with stab probe for taking core temperatures

### Applications

Liquid baths Recording thermometers for chillers and offices  
Applications requiring the meeting of Food Directive 92/1, such as E18-150.