



DATA SHEET

3Com® 11 Mbps Wireless LAN PCI Adapter

Key Benefits

Secure, reliable
desktop connections
without laying cables

Features and Benefits

Flexible

Allows fast, easy deployment and relocation of desktop systems in temporary offices or hard-to-wire areas without being limited by wired network infrastructure. Connects to compatible WLAN access points—or directly to other Wi-Fi certified client devices.

Secure

Supports 40-bit and 128-bit WEP encryption and 802.1x for increased security options with RADIUS authentication.*

Reliable

This wireless PCI card delivers reliable, wired-like LAN connections with speeds up to 11 Mbps and distances up to 100 meters (328 feet) indoors.†

Dynamic rate shifting keeps connections reliable—even in noisy environments.

Compatible

Supports a broad range of Windows operating systems. Wi-Fi certification ensures interoperability with Wi-Fi certified PC Cards, PCI cards, USB adapters, access points and bridges—from 3Com and other vendors.

Upgradable

Firmware upgradability lets you easily add new wireless and security features as they become available, preserving your PCI card investment.

Feature	Benefit
Security	
Encryption	Uses 40-bit and 128-bit WEP encryption, helping ensure all wireless transmissions remain private.
802.1x support	Provides RADIUS server authentication when used with Windows XP and an 802.1x-compatible access point.
Performance	
Wired-like network performance	Delivers up to 11 Mbps throughput at distances up to 100 meters (328 feet) indoors.
Dynamic rate shifting	Automatically adjusts between 11, 5.5, 2, and 1 Mbps for optimal connections as environmental conditions change.
External antenna	External antenna can help provide clear, interference-free reception.
Simplicity	
Wireless LAN Configuration Utility	Simplifies set up of user profiles.
Ad hoc networking	Connects multiple wireless clients without using access points.

* 802.1x capabilities require Windows XP and an 802.1x-compatible wireless access point.

† 100 m (328 ft) range depends on physical conditions and other electrical devices in the area.

Features and Benefits

Feature	Benefit
Simplicity	
Broad hardware and operating system compatibility	Supports PCI 2.2 standard and Windows XP, Me, 2000, 98 SE, 98, 95 OSR2, and Windows NT 4.0 operating systems; Wi-Fi certification ensures multivendor interoperability.
Designed for upgradability	Firmware upgradability lets you easily add new wireless and security features as they become available, preserving your PCI card investment.

Specifications

Standards Conformance IEEE 802.11b, 802.1x Wi-Fi certified PCI 2.2 ACPI 1.0 PCI Bus Power Management Interface Specification 1.0	Radio: FCC Part 15.247, RSS-210, EN 300 328-2 RF Exposure: FCC OET Bulletin 65 Supplement C, RSS-210, prEN 50371 European CE Conformance: EC Council R&TTE Directive 1999/5/EC	Frequency Range 2.400-2.4835 GHz, Direct Sequence Spread Spectrum (DSSS)
Data Rates 11 5.5, 2, and 1 Mbps; supports dynamic rate shifting	Physical Dimensions 64.41 mm x 119.91 mm x 1.65 mm (2.54 in x 4.72 in x 0.06 in)	Number of Channels Europe: 13 (1-13) France: 4 (10-13) U.S: 11 (1-11)
Management Wireless LAN Configuration Utility	Environmental Operating Ranges Ambient temperature: 0° to 55°C (operating), -20° to 65°C (storing) Max. humidity: 95% noncondensing	Antenna Type Detachable dipole antenna with SMA (male) connector
Bus Type PCI	Transmit Power +18 dBm @ nominal temporary (typical)	Connector Type Reverse SMA (female) connector
Security 40- and 128-bit WEP encryption 802.1x authentication	Operating Voltage 3.3 V and 5 V \pm 5% Current consumption 450 mA (typical) @ 3.3 V; 300 mA @ 5 V (typical)	LED Indicator Power LED (Green)
Operating Systems Windows XP, Me, 2000, 98 SE, 98, 95 OSR2, and Windows NT 4.0 (Service Pack 6 or above)		Mobility Seamless roaming across cell boundaries with handover
Safety and Electromagnetic Conformance Safety: EN 60950 EMC: FCC Part 15 Subpart B Class B, ICES-003, EN 301 489-17		Warranty Three-Year Limited warranty
		Customer Support Quick access to support information is available on 3Com's website at www.3com.com .

Ordering Information

Product Name	Region	Order Number
3Com 11 Mbps Wireless LAN PCI Adapter	Worldwide	3CRDW696
3Com 11 Mbps Wireless LAN PCI Adapter	Asia/Pacific Rim	3CRDW696-AP
3Com 11 Mbps Wireless LAN PCI Adapter	China	3CRDW696-CH

Please note: This product contains encryption and may require U.S. and/or local government authorization prior to export or import to another country.



3Com Corporation, Corporate Headquarters, 5400 Bayfront Plaza, P.O. Box 58145, Santa Clara, CA 95052-8145.

To learn more about 3Com solutions, visit www.3com.com. 3Com Corporation is publicly traded on Nasdaq under the symbol COMS.

Copyright © 2002 3Com Corporation. All rights reserved. 3Com and the 3Com logo are registered trademarks of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. Specifications subject to change without notice.

400773-001 07/02